



Characteristic Curves

TEQ 160-4812WIR


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEQ 160-4815WIR


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEQ 160-4816WIR


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEQ 160-4818WIR


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEQ 160-7212WIR


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEQ 160-7215WIR


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEQ 160-7216WIR


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEQ 160-7218WIR


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic



Remote on/off Voltage Start-Up Characteristic

